

Lithium-ion Cylindrical Battery 圆柱体锂离子电池

Model 型号	Nominal Voltage 标称电压(V)	Nominal Capacity 标称容量(mAh)		Cell dimensions 电池尺寸(mm)		Charge&Discharge 充电及放电		Temperature 温度 °C			Approximate Weight 大约重量(g)
		Typical 额定	Minimum 最小	Diameter 直径 (±0.2)	Height 高度 (±0.5)	Charge Current 充电电流	Discharge Current 放电电流	Charge 充电	Discharge 放电	Storage 库存	
ICR14430	3.7	650	600	14.0	42.5	0.5C	1C	0~45	-20~60	-20~35	17.0
ICR14500	3.7	800	700	14.0	48.5	0.5C	1C	0~45	-20~60	-20~35	20.0
ICR14650	3.7	1100	1050	14.0	64.5	0.5C	1C	0~45	-20~60	-20~35	24.0
ICR17280	3.7	600	550	17.0	27.5	0.5C	1C	0~45	-20~60	-20~35	15.0
ICR17335	3.7	700	650	17.0	33.5	0.5C	1C	0~45	-20~60	-20~35	18.0
ICR17500	3.7	1050	1000	17.0	48.5	0.5C	1C	0~45	-20~60	-20~35	27.0
ICR17650	3.7	1250	1200	17.0	64.5	0.5C	1C	0~45	-20~60	-20~35	37.0
ICR18500	3.7	1400	1350	18.3	48.5	0.5C	1C	0~45	-20~60	-20~35	34.0
ICR18650	3.7	1800	1800	18.3	64.5	0.5C	1C	0~45	-20~60	-20~35	45.0
ICR18650	3.7	2000	1950	18.3	64.5	0.5C	1C	0~45	-20~60	-20~35	45.0
ICR18650	3.7	2200	2150	18.3	64.5	0.5C	1C	0~45	-20~60	-20~35	45.0
ICR18650	3.7	2400	2300	18.3	65.5	0.6C	2C	0~46	-20~60	-20~35	45.0
ICR26650	3.7	3200	3100	26.0	64.5	0.5C	1C	0~45	-20~60	-20~35	65.0
ICR18650D	3.7	1400	1300	18.3	64.5	1C	10~20C	0~45	-20~60	-20~35	32.5
ICR18650TD	3.0	1300	1200	18.3	64.5	1C	3~5C	0~45	-20~60	-20~35	43.0
ICR18650TD	3.0	1100	1000	18.3	64.5	1C	10C	0~45	-20~60	-20~35	40.0
ICR18740TD	3.0	1600	1500	18.3	64.5	1C	10C	0~45	-20~60	-20~35	45.0
ICR17500TD	3.0	700	650	17.0	48.5	1C	10C	0~45	-20~60	-20~35	35.0
ICR18500TD	3.0	900	850	18.3	48.5	1C	10C	0~45	-20~60	-20~35	37.0
ICR26650TD	3.0	2400	2300	26.3	64.5	1C	10C	0~45	-20~60	-20~35	83.0
ICR32650TD	3.0	3800	3700	32.3	64.5	1C	10C	0~45	-20~60	-20~35	132.0